2026 CAN-AM OUTLANDER ELECTRIC



PACKAGE HIGHLIGHTS

- · Liquid-cooled system: Battery, inverter, motor and on-board charger
- Charging from 20% to 80% in as little as 50 min
- Up to 50 miles (80 km) of range
- · High and Low gears allow full work capacity
- · Engine modes and speed limiter
- Dedicated tyres for optimal noise and vibration level
 Description of the second seco
- 3-level regen braking
- · On-the-fly reverse capabilities
- · 5 in. coloured display
- Front and rear bumpers
- · LED headlights and taillights, specific LED POD light

MOTOR	
Туре	47 hp / 53 lb-ft, ROTAX® E-POWER, Liquid-cooled
Power	Peak: 47 hp (35 kW) Continuous: 27 hp (20.1 kW)
Torque Motor	Peak: 53 lb-ft (71.9 Nm) Continuous: 21 lb-ft (28.5 Nm)
Top Speed	High gear: 50 mph (80.5 km/h) Low gear: 28 mph (45.1 km/h)
BATTERY	
Battery Type	Integrated, lithium-ion
Battery Operating Temperature Range	From -20°C to 40°C (-4 Fahrenheit to 104 Fahrenheit)
Battery Capacity	8.9 kWh
Cooling System	Liquid-cooled: Battery, inverter and on-board charger Integrated AC heater for charging at low temperature
Estimated Range (when fully charged)	Tested in. accordance with WMTC*: 50 miles (80.5 km) Average utility range*: 31 miles (49.9 km)
Feature	Regen braking with 3 levels of adjustment
Charger	On-board charger 6.6 kW Level 2 (compatible with level 1 charging)
Connector Type	Type 1 J1772 with integrated LED light
Charging Time Level 2 (240 V)	50 min (20–80%) 1 hour 30 min (0–100%)
Charging Time Level 1 (120 V)	3 hours 10 min (20–80%) 5 hours 15 min (0–100%)
DRIVETRAIN	
Transmission	L/N/H/P Reverse activated via start button
Drive Train	Selectable 2WD / 4WD with Visco-Lok† QE auto-locking front differential
Driving Assistance	Work / Standard / Sport modes Speed limiter
Power Steering	Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Double A-arm 9.75 in. (24.8 cm) travel
Front Shocks	Twin-tube
Rear Suspension	Double A-arm 10.25 in. (26 cm) travel
Rear Shocks	Twin-tube

TYRES & WHEELS

110110	AT O NECOTT OFCE 20 X 0 X 14 III.
Rear	XPS Recon Force 26 x 10 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm disc brake

VDC Docon Force 26 v 0 v 14 in

DIMENSIONS & CAPACITIES

Estimated Dry Weight**	875 lb (396.9 kg)
LxWxH	86.7 x 47.6 x 48 in. (220.2 x 120.9 x 121.9 cm)
Wheelbase	53 in. (134.6 cm)
Ground Clearance	12 in. (30.5 cm)
Seat Height	38 in. (96.5 cm)
Rack Capacity	Front: 120 lb (54.4 kg) Rear: 240 lb (108.9 kg)
Storage Capacity	9 gal (34.1 L)
Towing Capacity	1,830 lb (830.1 kg)
Person Capacity	1

FEATURES

WADDANTY	
Hitch Type	2 in. hitch receiver
Protection	Front and rear bumpers Full skid plate
Handlebar	Standard
Seat	Standard
Winch	N/A
Lighting	LED headlights and taillights LED signature lights LED POD light
Ignition	RF Digitally Encoded Security System (D.E.S.S.™)
Instrumentation	Phone charger with 1xUSB-A and 1xUSB-C outputs
DC-DC Converter	Continuous 500W (at all speeds including at idle)
Gauge	5 in. coloured display

WARRANTY

Factory Warranty	Battery: 5 years (12,427 miles / 20,000 km limit)
	3-year unlimited km powertrain & Rotax® engine warranty
	and 1-year warranty & unlimited km on the rest of the unit









